



# BFGoodrich® HIGHWAY CONTROL® T




# **GO THE DISTANCE**

BFGoodrich® tires are built to go the distance. Each tire is constructed with a premium casing and tread that is designed to enhance even wear.

#### LONG TREAD LIFE

Expect long tread life and exceptional even wear performance

- Shoulder decoupling groove with micro sipes help fight the onset of irregular wear.
- Consistent manufacturing process which contributes to trailer tire tread life.



#### MULTIPLE RETREAD LIVES

#### Legendary BFGoodrich® casing

- Excellent retreadability
- · Durability keeps you up and running.





#### EVEN WEAR OVER THE LONG HAUL.


If you are not completely satisfied with the BFGoodrich® HIGHWAY CONTROL® T tire even wear performance in the first two (2) years or before 50% of its usable tread life—which ever comes first we will reimburse 50% of your acquisition price per tire. (2)





### ALL SEASON CONFIDENCE

Pass-thru groove design for outstanding water evacuation





## **FUEL EFFICIENCY**

New sidewall compounds designed for fuel efficiency without sacrificing wear. (3)





Size	Load Range	Catalog Number		Max. Speed (4)				_	Overall Over iameter		l Width 5)	Approved Wheels (Measuring wheel	Min. Dual Spacing (5)		Revs Per	Max. Load Per Tire Single				Max. Load Per Tire Dual			
			32nds	mph	km/h	in.	mm.	in.	mm.	in.	mm.	listed first)	in.	mm.	Mile	lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
11R22.5	G	97956	12	75	120	19.1	484	40.9	1038	11.2	284	8.25, 7.50	12.5	318	507	6175	105	2800	720	5840	105	2650	720
275/80R22.5	G	70298	12	75	120	18.5	470	39.7	1008	11.1	283	8.25, 7.50	12.2	311	522	6175	110	2800	760	5675	110	2575	760
11R24.5	G	44529	12	75	120	20.0	507	42.9	1089	11.2	285	8.25, 7.50	12.5	318	483	6610	105	3000	720	6005	105	2725	720
285/75R24.5	G	26773	12	75	120	19.1	486	40.8	1037	10.7	273	8.25	12.5	318	507	6175	110	2800	760	5675	110	2575	760

Note: Wheel listed first is the measuring wheel.

- (1) 5 Year / 2-Retread Limited Casing Guarantee when retreaded by an authorized Michelin Retread Technologies (MRT) Dealer or an Oliver Retread dealer.
- Please see BFGoodrichTruckTires.com > Reference Manuals > Warranties/Guarantees for details.
- (3) Based on internal rolling resistance tests using ISO 28580 test method comparing the BFGoodrich® TR144 vs BFGoodrich® Highway Control® T tire in the 275/80R22.5 LRG size. Actual fuel saving results may vary, and may be impacted by many factors, to include road conditions, weather, environment, combination of steer and trailer tires used, driving habits, tire size, equipment and maintenance.

Exceeding the lawful speed limit is neither recommended nor endorsed.

(5) Tire section widths and overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.

BEGoodrich® tires are subject to a continuous development program. BEGoodrich® Commercial Truck Tires reserves the right to change product specifications at any time without notice or obligation

MNA, Inc. continually updates its product information to reflect any changes in Industry Standards. Printed material may not reflect the current Load and Inflation information. Please visit www.bfgoodrichtrucktires.com for the latest product information. The actual load and inflation pressure used must not exceed the wheel manufacturer's maximum conditions. Never exceed a wheel manufacturer's limits without permission from the component manufacturer.

Application	Highway	Regional		Urban	Coad	ch/Bus	On/ Off-Road		
Position	Stee	r		Drive		Trailer			
Recommended Application Acceptable Application									

# » Take control today at BFGoodrichTruckTires.com

To Find Your Nearest BFGoodrich® Commercial Truck Tire Dealer Call: United States, 1-877-788-8899; Canada, 1-888-871-6666 or visit www.bfgoodrichtrucktires.com

© 2020 MNA, Inc. All rights reserved. BWL30001 (04/20)

© 2020 MNA(C)I All rights reserved. (04/20)