

BFGoodrich® ST230

Take control in and out of the city with this curb-fighting, smooth-wearing steer/all-position regional tire that's SmartWay® verified.

SmartWay Verified





CONQUERS THE CURBS

» Bump and bruise resistant



FIGHTS IRREGULAR WEAR


» Smooth, even-wearing tread



RETREADABILITY **COMES STANDARD**

» Multiple lives

5 Year / 2-Retread Manufacturer's Limited Casing Guarantee







Application	Highway	Regio	nal	Urban	Co E	ach/ Sus	On/ Off-Road		
Position	Stee	r		Drive		7	Trailer		
	d Application			ble Applicat					

Size		Catalog Number	Depth	(1)	Loaded Radius		Overall Diameter		Overall Width (2)		Wheels	Min. Dual Spacing (2)		Revs Per	Max. Load Per Tire Single			Max. Load Per Tire Dual				
					in.	mm.	in.	mm.	in.	mm.	(Measuring wheel listed first)	in.	mm.	Mile	lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
10R22.5	G	62086	17	75	18.6	472	39.8	1012	10.0	255	7.50, 6.75, 8.25	11.4	288	521	5675	115	2575	790	5355	115	2430	790
255/70R22.5	Н	95971	17	75	17.1	435	36.6	929	10.2	258	8.25, 7.50	11.6	295	566	5510	120	2500	830	5070	120	2300	830
315/80R22.5 (4)	L	55458	17	75	19.6	499	42.4	1077	12.5	317	9.00, 9.75	13.8	351	489	9090	130	4125	900	8270	130	3750	900

Note: Wheel listed first is the measuring wheel.

- (1) Exceeding the lawful speed limit is neither recommended nor endorsed.
- (2) Tire section widths and overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.
- (3) 5 Year / 2-Retread Limited Casing Guarantee when retreaded by an authorized Michelin Retread Technologies (MRT) Dealer or an Oliver Retread dealer. See www.bfgoodrichtrucktires.com for more information.
- (4) Not approved for use with an 8.25 wheel.

BFGoodrich® tires are subject to a continuous development program. BFGoodrich® Commercial Truck Tires reserves the right to change product specifications at any time without notice or obligation.

» Take control today at BFGoodrichTruckTires.com.

