

BFGoodrich® DR454

Take control of your business with this fuel-saving, rain-fighting highway drive tire that's SmartWay® verified.







MAX FUEL EFFICIENCY

» Less stops at the pump



SERIOUS GRIP

» Bring on the rain



RETREADABILITY COMES STANDARD

» Multiple lives









Application	Highway	Regional		Urban		ach/ Bus	On/ Off-Road				
Position	Stee	r		Drive		1	Гrailer				
Recommended Application Acceptable Application											

Size		ge Number		Speed (1)	Loaded Radius		Overall Diameter		Overall Width (2)		Approved Wheels (Measuring wheel	Min. Dual Spacing (2)		Revs Per	Max. Load Per Tire Single			Max. Load Per Tire Dual				
	Kange				in.	mm.	in.	mm.	in.	mm.	listed first)	in.	mm.	Mile	lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
11R22.5	G	06941	26	75	19.5	496	41.8	1061	11.2	284	8.25, 7.50	12.5	318	496	6175	105	2800	720	5840	105	2650	720
275/80R22.5	G	05887	26	75	19.0	482	40.6	1031	10.9	277	8.25, 7.50	12.2	311	510	6175	110	2800	760	5675	110	2575	760

Note: Wheel listed first is the measuring wheel.

(1) Exceeding the lawful speed limit is neither recommended nor endorsed.

(2) Tire section widths and overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.

(3) 5 Year / 2-Retread Limited Casing Guarantee when retreaded by an authorized Michelin Retread Technologies (MRT) Dealer or an Oliver Retread dealer. See www.bfgoodrichtrucktires.com for more information.

BFGoodrich® tires are subject to a continuous development BFGoodrich® tires are subject to a continuous development program. BFGoodrich® Commercial Truck Tires reserves the right to change product specifications at any time without notice or obligation.

» Take control today at BFGoodrichTruckTires.com.

