



LINE HAUL APPLICATIONS

THE MICHELIN® X ONE® LINE ENERGY D2 TIRE

Our lowest rolling resistance heavy truck drive tire to date, for truckload, long haul transportation. Designed for industry-leading fuel savings to lower total cost of ownership while providing exceptional traction for driver confidence.

Line Haul	Regional	Urban	On/Off Road
Recommended	Acceptable		

SmartWay®
Verified



DIRECTIONAL TIRE
(For 1st Half of Life)



**Exceptional
Fuel Savings**

**Driver
Confidence**

**Maximum
Retreadability**

**Low Total Cost
of Ownership**

* Meets SmartWay® requirement for a drive tire. Application pending.

business.michelinman.com



MICHELIN

THE MICHELIN® X ONE® LINE ENERGY D2 TIRE

Our lowest rolling resistance heavy truck drive tire to date, for truckload, long haul transportation. Designed for industry-leading fuel savings to lower total cost of ownership while providing exceptional traction for driver confidence.

SmartWay®
Verified

Exceptional Fuel Savings

• Advanced Tread Compound

- MICHELIN® X One® Line Energy D2 tires save USD \$2,317 [CAD 3,518 \$] per year vs Bridgestone® Greatec M835A Ecopia™ tires. ^(1,2)

• Reduced Carbon Output

- New ultra low rolling resistance levels designed to exceed SmartWay, CARB and GHG2 requirements

• Compact Tread Design

- Designed for less tread squirm, providing energy conservation for fuel efficiency


Driver Confidence

• Regenion Evolving Tread Design

- Provides stability in all weather conditions
- Delivers long lasting traction
- Straight, pass-thru grooves with evolving features appear later in tread life for long-lasting traction.



New - 20/32nds



14/32nds



5/32nds

Maximum Retreadability

• Rectangular bead bundle

- Stabilizes bead region and minimizes fatigue to extend casing life

• Designed for durability and multiple retread lives

• Directional Design

- Provides improved resistance to irregular wear for driver satisfaction and long tread life.



DIRECTIONAL TIRE
(For 1st Half of Life)



MICHELIN X ONE TOTAL SATISFACTION GUARANTEE

- **Your Drivers:** Not satisfied with the traction and handling?
 - We'll issue a credit for the original value of the tire plus help fund the dealer service work.
- **You:** Not satisfied with the performance of mileage, weight savings, fuel savings, or retreadability at runout?
 - We'll issue a credit to buy back the used casing and wheel.
- **Guidelines and exclusions apply.** Please see business.michelinman.com/tips-suggestions/documents

Size	Load Range	Catalog Number	Tread Depth	Max. Speed ⁽⁴⁾		Loaded Radius		Overall Diameter		Overall Width ^(‡)		Approved Wheel	Revs Per Mile	Max. Load and Pressure Single			
			32nds	mph	kph	in.	mm	in.	mm	in.	mm			lbs.	psi	kg.	kPa
445/50R22.5 ⁽¹⁾	L	26760	20	75	120	18.6	472	40.1	1020	17.1	434	14.00	518	10200	120	4625	830

* Meets SmartWay® requirement for a drive tire. Application pending.

(1) Based on MVTs third party testing of 445/50R22.5 drive tires. When fitted on a 2019 International LT 625's with Cummins X15 15-Liter engines and Eaton Endurant 12-speed Automated Manual Transmissions, with a 53' Hyundai dry van, loaded to 78,000 lbs., running at 65mph, at \$2.551/gallon fuel price (2020 average, <https://www.eia.gov>).

(2) Based on US testing, conversion to Canadian currency at CAD 1.024/liter (2020 average diesel price, <https://data.ontario.ca/dataset/fuels-price-survey-information>).

(3) Directional tread design.

(4) Exceeding the lawful speed limit is neither recommended nor endorsed.

(‡) Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width.

MICHELIN® tires and tubes are subject to a continuous development program. Michelin North America, Inc. reserves the right to change product specifications at any time without notice or obligations. MNA, Inc. continually updates its product information to reflect any changes in Industry Standards. Printed material may not reflect the current Load and Inflation information. Please visit business.michelinman.com for the latest product information. The actual load and inflation pressure used must not exceed the wheel manufacturer's maximum conditions. Never exceed a wheel manufacturer's limits without permission from the component manufacturer.

TO FIND OUT MORE
US: business.michelinman.com
CA: business.michelin.ca

FIND US ON FACEBOOK
[michelintruck](https://www.facebook.com/michelintruck)

@ CONTACT US ON THE WEB
US: business.michelinman.com/contact-us
CA: business.michelin.ca/contact-us

CONTACT US BY TELEPHONE
US: 1-888-622-2306
CA: 1-888-622-2306