



LINE HAUL APPLICATIONS

THE MICHELIN® X® LINE ENERGY T (19.5") TIRE

Fuel-efficient⁽¹⁾, long wearing, small diameter trailer tire designed for high cube service in line haul applications.

Line Haul	Regional	Urban	On/Off Road
Recommended	Acceptable		



(1) Based on industry standard rolling resistance testing of comparable trailer tires. Actual results may vary, and may be impacted by many factors, to include road conditions, weather and environment, driver performance, etc.

business.michelinman.com



MICHELIN

THE MICHELIN® X® LINE ENERGY T (19.5") TIRE

Fuel-efficient⁽¹⁾, long wearing, small diameter trailer tire designed for high cube service in line haul applications.

Fuel Efficiency

- **Specially Engineered Rubber Compound**
Reduces rolling resistance.

Longer Tread Life

- **Wider Tread**
Distributes force.
- **Massive Shoulders**
Resists scuffing.
- **Micro Sipes**
Help prevent abnormal wear.

Driver Confidence

Wet surface grip

- **See-Through Circumferential Grooves**
Promotes efficient water evacuation for good wet braking and traction throughout the tread life.
- **Hydro Sipes**
Improves traction in wet conditions.

Extended Casing Life

Longer life and retreadability.

- **Rectangular Bead Bundle**
A Michelin exclusive – simulates a solid steel rod “strapping” the tire onto the wheel. This design stabilizes the entire bead region and minimizes fatigue in order to extend casing life.
- **Extended Metallic Chafer**
Provides increased protection against mounting damage and brake heat.

(1) Based on industry standard rolling resistance testing of comparable trailer tires. Actual results may vary, and may be impacted by many factors, to include road conditions, weather and environment, driver performance, etc.

Size	Load Range	Catalog Number	Tread Depth	Max. Speed (*)		Loaded Radius		Overall Diameter		Overall Width (‡)		Approved Wheels	Min. Dual Spacing (‡)		Revs Per Mile	Max. Load and Pressure Single				Max. Load and Pressure Dual			
			32nds	mph	kph	in.	mm	in.	mm	in.	mm		in	mm		lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
265/70R19.5	J	83809	13	62	100	15.7	399	33.9	862	10.4	265	7.50, 6.75, 8.25	11.8	300	608	6005	123	2725	850	5675	123	2575	850

(*) Exceeding the lawful speed limit is neither recommended nor endorsed.

(‡) Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.

MICHELIN® tires and tubes are subject to a continuous development program. Michelin North America, Inc. reserves the right to change product specifications at any time without notice or obligations.

MNA, Inc. continually updates its product information to reflect any changes in Industry Standards. Printed material may not reflect the current Load and Inflation information. Please visit business.michelinman.com for the latest product information. The actual load and inflation pressure used must not exceed the wheel manufacturer's maximum conditions. Never exceed a wheel manufacturer's limits without permission from the component manufacturer.

TO FIND OUT MORE
US: business.michelinman.com
CA: business.michelin.ca

FIND US ON FACEBOOK
[michelintruck](https://www.facebook.com/michelintruck)

VISIT US ON THE WEB
US: business.michelinman.com/contact-us
CA: business.michelin.ca/en/contact-us

CONTACT US BY TELEPHONE
US: 1-888-622-2306
CA: 1-888-622-2306

Michelin North America Inc., One Parkway South, Greenville, SC 29615

Michelin North America (Canada) Inc., 1001, De Maisonneuve Boulevard W, 10th Floor, Montreal, QC H3A 3C8

Copyright © 2026 MNA(C)I. All rights reserved.

Copyright © 2026 Michelin North America, Inc. All rights reserved. An Equal Opportunity Employer PDF Only (07/26)