









MICHELIN XTXL



LOAD CAPACITY

*** 3 Star load capacity with the new reinforced cable technology

Offers 10%⁽¹⁾ Highest strength and cable density versus XLDD1.

DURABILITY

Reinforced crown and sidewall resistance to agression

Provides +40% metal mass, +50% thicker sidewall compared to the XLDD1⁽²⁾. A4 compound for high cut resistance available.



PRODUCTIVITY

Increased contact with the wheel and increased clamping force

Maximizes torque transmission for a better productivity with a wider bead design (+30%) on the rim versus XLDD1⁽²⁾.

TIRE CHARACTERISTICS

ADDITIONAL INFORMATIONS

APPLICABLE VEHICLES





MICHELIN XTXL is designed for the highest load condition in very abrasive soil, a reference for the block Handling application with high sidewall protection

> **Product Manager** Michelin Group



(1) Internal comparison between Michelin® XTXL 29.5R25 and Michelin® XLD D1 29.5R25. Measurement certified by Michelin center of technology, Reference Michelin® Technical Earthmover Data Book 2023. (2) Internal comparison between Michelin® XTXL 29.5R25 and Michelin® XLD D1 29.5R25. Measurement certified by Michelin center of technology, Reference Michelin® Technical Earthmover Data Book 2019.

LEARN MORE

ON THE WEB https://business.michelinman.com/tires/michelin-

CONTACT

Please contact your local sales representative for more information.

