MICHELIN
YIELDBIB

RADIAL
TYRE



THE LOW-PRESSURE TIRE FOR HIGH-POWERED ROW CROP APPLICATIONS

CROP FARMING
SEGMENT

MICHELIN

MICHELIN YIELDBIB

1 TRACTION

Improve your productivity
Thanks to 45° designed lugs[1]. Same load capacity with 40% lower pressure.

2 YIELD IMPROVEMENT

Increase your yield
Thanks to 27% bigger footprint[2] and the MICHELIN UltraFlex technologies.

3 ROBUSTNESS

Greater stubble resistance
Additional reinforcement in the center of the tread to defend against stubble. Exclusive rubber compound for added durability against chipping from stubble.

TYRE CHARACTERISTICS



ADDITIONAL INFORMATION

APPLICABLE VEHICLES





MICHELIN YIELDBIB tires floats over the soil, while the other tires sinks and leaves ruts

Product Category Manager
Michelin Group

[1] Compared to standard competitor's tires with 23° lugs.
[2] Michelin test 2016, VF 480/80R50 YIELDBIB vs 480/80R50 AGRIBIB.

ON THE WEB

CONTACT

Please contact your local sales representative for more information.

UPDATED JUN 2026

MICHELIN YIELDBIB

ON THE WEB

TYRE CHARACTERISTICS

Load capacity (kg & pound) based on inflation pressure (bar & psi) and speed (km/h & mph).

Description	CAI *[MSPN]*	Overall Width mm	Overall Diameter mm	Static load radius mm	Rolling circumference mm	75% internal volume liter	Recommended Rim	Other approved rims mm	Tube [code]	Minimum Dual Spacing mm
VF 380/85R34 149A8/149B TL	**305457** *91239*	**372**	**1510**	**668**	**4471**	**230**	**W13x34**	**W12x34**	**171115** *[704]*	**510**

BAR	0.4	0.5	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.4	1.6
10 KM/H	1595	1760	1925	2090	2255	2420	2585	2750	2915	3245	3575
30 KM/H	1480	1630	1785	1940	2090	2245	2400	2550	2705	3010	3315
50 KM/H	1450	1600	1750	1900	2050	2200	2350	2500	2650	2950	3250
30 KM/H DUAL	1300	1435	1570	1705	1840	1975	2110	2245	2380	2650	2915
50 KM/H DUAL	1280	1410	1540	1675	1805	1940	2070	2200	2335	2600	2860
30 KM/H TRIPLE	1215	1340	1465	1590	1715	1840	1970	2095	2220	2470	2720
50 KM/H TRIPLE	1190	1310	1435	1560	1680	1805	1930	2050	2175	2420	2665

Description	CAI *[MSPN]*	Overall Width mm	Overall Diameter mm	Static load radius mm	Rolling circumference mm	75% internal volume liter	Recommended Rim	Other approved rims mm	Tube [code]	Minimum Dual Spacing mm
VF 420/85R34 154A8/154B TL	**012445** *58965*	**432**	**1582**	**699**	**4682**	**287**	**DW15Lx34**	**W13x34* W14Lx34 DW14A(L)x34**	**171115** *[704]*	**554**

BAR	0.4	0.5	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.4	1.6
10 KM/H	1870	2060	2250	2440	2630	2820	3010	3195	3385	3755	4125
30 KM/H	1735	1910	2090	2265	2440	2615	2790	2960	3135	3480	3825
50 KM/H	1700	1870	2045	2220	2390	2560	2730	2905	3075	3410	3750
30 KM/H DUAL	1525	1680	1835	1990	2145	2300	2450	2605	2760	3060	3365
50 KM/H DUAL	1500	1650	1800	1955	2105	2255	2405	2555	2705	3000	3300
30 KM/H TRIPLE	1425	1570	1710	1855	2000	2140	2285	2430	2570	2850	3135
50 KM/H TRIPLE	1395	1535	1680	1820	1960	2100	2240	2380	2520	2800	3075

***Other approved rims W15A(L)x34**

* IMPORTANT

The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (October 2026). Technical data is subject to change without prior notice.

- For plowing and other field applications subject to high torque, use the 30 km/h line.
- When using single tire configuration:
  - add 0.4 bar for use on slopes of more than 20%
  - add 0.4 bar for intensive road use exceeding 50%
- 10 km/h: low torque application only.

MICHELIN YIELDBIB

ON THE WEB

TYRE CHARACTERISTICS

Load capacity (kg & pound) based on inflation pressure (bar & psi) and speed (km/h & mph).

Description	CAI *[MSPN]*	Overall Width mm	Overall Diameter mm	Static load radius mm	Rolling circumference mm	75% internal volume liter	Recommended Rim	Other approved rims mm	Tube [code]	Minimum Dual Spacing mm
VF 380/80R38 149A8/149B TL	**870363** *35470*	**366**	**1592**	**711**	**4851**	**230**	**DW12Ax38**	**W12x38 W13x38**	**170079 118826** *[795] [796]*	**510**

BAR	0.4	0.5	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.4	1.6
10 KM/H	1595	1760	1930	2095	2260	2425	2590	2755	2920	3250	3575
30 KM/H	1480	1635	1790	1940	2095	2250	2400	2555	2710	3010	3315
50 KM/H	1450	1600	1750	1905	2055	2205	2355	2505	2655	2950	3250
30 KM/H DUAL	1300	1435	1570	1710	1845	1980	2115	2250	2385	2650	2915
50 KM/H DUAL	1280	1415	1550	1680	1815	1945	2080	2210	2340	2600	2860
30 KM/H TRIPLE	1215	1340	1470	1595	1720	1845	1970	2095	2220	2470	2720
50 KM/H TRIPLE	1190	1315	1440	1560	1685	1810	1930	2055	2180	2420	2665

VF 380/95R38 154A8/154B TL	**873023** *47253*	**377**	**1703**	**755**	**5044**	**286**	**DW12Ax38**	**W12x38**	**170079 118826** *[795] [796]*	**510**

BAR	0.4	0.5	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.4	1.6
10 KM/H	1870	2060	2250	2435	2625	2810	3000	3185	3370	3750	4125
30 KM/H	1735	1910	2085	2260	2435	2610	2780	2950	3125	3475	3825
50 KM/H	1700	1870	2040	2215	2385	2555	2725	2895	3065	3410	3750
30 KM/H DUAL	1525	1680	1835	1990	2145	2295	2450	2600	2750	3060	3365
50 KM/H DUAL	1500	1650	1800	1950	2100	2250	2400	2550	2700	3000	3300
30 KM/H TRIPLE	1425	1570	1710	1850	1995	2140	2280	2420	2565	2850	3135
50 KM/H TRIPLE	1400	1540	1680	1815	1955	2095	2235	2375	2515	2795	3075

* IMPORTANT

The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (October 2026). Technical data is subject to change without prior notice.

- For plowing and other field applications subject to high torque, use the 30 km/h line.
- When using single tire configuration:
  - add 0.4 bar for use on slopes of more than 20%
  - add 0.4 bar for intensive road use exceeding 50%
- 10 km/h: low torque application only.

MICHELIN YIELDBIB

ON THE WEB

TYRE CHARACTERISTICS

Load capacity (kg & pound) based on inflation pressure (bar & psi) and speed (km/h & mph).

Description	CAI *[MSPN]*	Overall Width mm	Overall Diameter mm	Static load radius mm	Rolling circumference mm	75% internal volume liter	Recommended Rim	Other approved rims mm	Tube [code]	Minimum Dual Spacing mm
VF 420/85R38 155A8/155B TL	**087051** *17647*	**432**	**1697**	**742**	**5010**	**311**	**DW15Lx38**	**DW14Lx38 W14Lx38 W15Lx38**	**170076** *[786]*	**554**

BAR	0.4	0.5	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.4	1.6
10 KM/H	1965	2160	2360	2555	2750	2950	3145	3340	3540	3930	4325
30 KM/H	1825	2005	2190	2370	2550	2735	2915	3100	3280	3645	4010
50 KM/H	1785	1965	2145	2320	2500	2680	2860	3030	3200	3535	3875
30 KM/H DUAL	1605	1765	1925	2085	2245	2405	2565	2725	2885	3210	3530
50 KM/H DUAL	1575	1730	1890	2045	2200	2360	2515	2670	2830	3145	3460
30 KM/H TRIPLE	1495	1645	1795	1940	2090	2240	2390	2540	2690	2990	3290
50 KM/H TRIPLE	1465	1610	1760	1905	2050	2200	2345	2490	2640	2930	3225

VF 420/85R42 163D/159E TL	**029153** *33231*	**436**	**1775**	**799**	**5278**	**335**	**DW15Lx42**	**DW14Lx42 W15Lx42 W14Lx42**	**170084** *[801]*	**554**

BAR	0.4	0.5	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.4	1.6	1.8	2.0	2.2	2.4
10 KM/H	2065	2270	2480	2685	2890	3100	3305	3510	3715	4130	4545	4780	4985	5150	5310
30 KM/H	1915	2110	2300	2490	2680	2870	3065	3255	3445	3830	4215	4430	4625	4775	4925
65 KM/H	1875	2065	2255	2440	2630	2820	3005	3190	3380	3755	4130	4345	4535	4705	4875
30 KM/H DUAL	1685	1855	2025	2190	2360	2530	2695	2860	3030	3370	3710	3900	4070	4200	4335
65 KM/H DUAL	1650	1820	1985	2150	2315	2480	2645	2810	2975	3305	3635	3825	3990	4140	4290
30 KM/H TRIPLE	1570	1730	1885	2040	2200	2360	2515	2670	2825	3140	3455	3635	3795	3920	4040
65 KM/H TRIPLE	1540	1690	1845	2000	2155	2310	2465	2620	2770	3080	3385	3565	3715	3860	4000

* IMPORTANT

The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (October 2026). Technical data is subject to change without prior notice.

- For plowing and other field applications subject to high torque, use the 30 km/h line.
- When using single tire configuration:
  - add 0.4 bar for use on slopes of more than 20%
  - add 0.4 bar for intensive road use exceeding 50%
- 10 km/h: low torque application only.

MICHELIN YIELDBIB

ON THE WEB

TYRE CHARACTERISTICS

Load capacity (kg & pound) based on inflation pressure (bar & psi) and speed (km/h & mph).

Description	CAI *[MSPN]*	Overall Width mm	Overall Diameter mm	Static load radius mm	Rolling circumference mm	75% internal volume liter	Recommended Rim	Other approved rims mm	Tube [code]	Minimum Dual Spacing mm
VF 380/85R46 159D/155E TL	**064980** *68748*	**380**	**1808**	**822**	**5384**	**287**	**W13x46**	**DW12x46 W12x46 DW13x46**	**203376** *[835]*	**510**

BAR	0.4	0.5	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.4	1.6	1.8	2.0	2.2	2.4
10 KM/H	1865	2050	2240	2425	2610	2795	2980	3170	3355	3730	4100	4300	4500	4645	4790
30 KM/H	1730	1900	2075	2250	2420	2590	2765	2940	3110	3455	3800	3985	4170	4310	4445
65 KM/H	1695	1865	2035	2200	2370	2540	2710	2880	3050	3385	3725	3910	4090	4230	4375
30 KM/H DUAL	1520	1670	1825	1975	2130	2280	2430	2585	2735	3040	3345	3510	3670	3790	3910
65 KM/H DUAL	1490	1640	1790	1940	2085	2235	2385	2535	2685	2980	3280	3440	3600	3720	3835
30 KM/H TRIPLE	1415	1555	1700	1840	1980	2125	2265	2405	2550	2830	3115	3270	3420	3530	3645
65 KM/H TRIPLE	1390	1530	1670	1805	1945	2085	2220	2360	2500	2780	3055	3205	3355	3460	3570

Description	CAI *[MSPN]*	Overall Width mm	Overall Diameter mm	Static load radius mm	Rolling circumference mm	75% internal volume liter	Recommended Rim	Other approved rims mm	Tube [code]	Minimum Dual Spacing mm
VF 480/80R46 164A8/164B TL	**842300** *10807*	**480**	**1933**	**861**	**5732**	**449**	**DW16Ax46**	**DW15Lx46* DW16Bx46 DW16Lx46**	**467962**	**626**

BAR	0.4	0.5	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.4	1.6
10 KM/H	2530	2780	3025	3270	3520	3770	4015	4260	4510	5005	5500
30 KM/H	2345	2575	2805	3035	3265	3495	3720	3950	4180	4640	5100
50 KM/H	2300	2525	2750	2975	3200	3425	3650	3875	4100	4550	5000
30 KM/H DUAL	2065	2270	2470	2670	2875	3075	3280	3480	3680	4085	4490
50 KM/H DUAL	2025	2220	2420	2620	2815	3015	3210	3410	3610	4005	4400
30 KM/H TRIPLE	1925	2110	2300	2490	2675	2865	3050	3240	3430	3805	4180
50 KM/H TRIPLE	1885	2070	2255	2440	2625	2810	2990	3175	3360	3730	4100

***Other approved rims W16Ax46**

* IMPORTANT

The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (October 2026). Technical data is subject to change without prior notice.

- For plowing and other field applications subject to high torque, use the 30 km/h line.
- When using single tire configuration:
  - add 0.4 bar for use on slopes of more than 20%
  - add 0.4 bar for intensive road use exceeding 50%
- 10 km/h: low torque application only.

MICHELIN YIELDBIB

ON THE WEB

TYRE CHARACTERISTICS

Load capacity (kg & pound) based on inflation pressure (bar & psi) and speed (km/h & mph).

Description	CAI *[MSPN]*	Overall Width mm	Overall Diameter mm	Static load radius mm	Rolling circumference mm	75% internal volume liter	Recommended Rim	Other approved rims mm	Tube [code]	Minimum Dual Spacing mm
VF 480/80R50 166A8/166B TL	**309830** *02098*	**468**	**2039**	**901**	**6034**	**479**	**DW16A(L) x50**	**DW15B(A)x50* DW15Lx50 DW16Bx50**		**626**

BAR	0.4	0.5	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.4	1.6
10 KM/H	2595	2855	3115	3375	3635	3895	4155	4415	4675	5250	5830
30 KM/H	2405	2645	2890	3130	3370	3610	3850	4095	4335	4870	5405
50 KM/H	2360	2595	2830	3070	3305	3540	3780	4015	4250	4775	5300
30 KM/H DUAL	2115	2330	2540	2750	2965	3180	3390	3600	3815	4285	4755
50 KM/H DUAL	2075	2285	2490	2700	2910	3120	3325	3530	3740	4200	4660
30 KM/H TRIPLE	1970	2170	2370	2565	2765	2960	3160	3360	3555	3990	4430
50 KM/H TRIPLE	1930	2125	2320	2515	2710	2905	3100	3295	3490	3920	4350

***Other approved rims W15B(A)x50, W16Bx50**

Description	CAI *[MSPN]*	Overall Width mm	Overall Diameter mm	Static load radius mm	Rolling circumference mm	75% internal volume liter	Recommended Rim	Other approved rims mm	Tube [code]	Minimum Dual Spacing mm
VF 480/95R50 170A8/170B TL	**252129** *65206*	**477**	**2186**	**962**	**6464**	**593**	**DW16Lx50**	**W16Lx50 DW15Lx50 [NRO] W15Lx50 [NRO]**		**626**

BAR	0.4	0.5	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.4	1.6
10 KM/H	3000	3310	3625	3940	4250	4560	4875	5190	5500	6050	6600
30 KM/H	2780	3070	3360	3650	3940	4230	4520	4810	5100	5610	6120
50 KM/H	2725	3010	3295	3580	3865	4150	4430	4715	5000	5500	6000
30 KM/H DUAL	2445	2700	2955	3210	3465	3720	3980	4235	4490	4940	5385
50 KM/H DUAL	2400	2650	2900	3150	3400	3650	3900	4150	4400	4840	5280
30 KM/H TRIPLE	2280	2520	2755	2990	3230	3470	3705	3940	4180	4600	5020
50 KM/H TRIPLE	2235	2470	2700	2935	3170	3400	3635	3870	4100	4510	4920

* IMPORTANT

The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (October 2026). Technical data is subject to change without prior notice.

- For plowing and other field applications subject to high torque, use the 30 km/h line.
- When using single tire configuration:
  - add 0.4 bar for use on slopes of more than 20%
  - add 0.4 bar for intensive road use exceeding 50%
- 10 km/h: low torque application only.

MICHELIN YIELDBIB

ON THE WEB

TYRE CHARACTERISTICS

Load capacity (kg & pound) based on inflation pressure (bar & psi) and speed (km/h & mph).

Description	CAI *[MSPN]*	Overall Width mm	Overall Diameter mm	Static load radius mm	Rolling circumference mm	75% internal volume liter	Recommended Rim	Other approved rims mm	Tube [code]	Minimum Dual Spacing mm
VF 480/95R54 177D/173E TL	**057539** *75847*	**493**	**2271**	**1015**	**6739**	**629**	**DW16Lx54**	**DW15Lx54 [NRO] W16Lx54 W15Lx54 [NRO]**		**626**

BAR	0.4	0.5	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.4	1.6	1.8	2.0	2.2	2.4
10 KM/H	3140	3450	3765	4080	4395	4705	5020	5335	5650	6275	6905	7240	7580	7825	8070
30 KM/H	2910	3200	3495	3785	4075	4370	4660	4950	5240	5825	6405	6715	7025	7255	7485
65 KM/H			3425	3710	3995	4280	4565	4850	5140	5710	6280	6585	6890	7135	7300
30 KM/H DUAL	2560	2820	3075	3330	3585	3845	4100	4355	4610	5125	5635	5910	6185	6385	6585
65 KM/H DUAL			3015	3265	3515	3770	4020	4270	4520	5025	5525	5795	6065	6260	6455
30 KM/H TRIPLE	2385	2625	2865	3105	3340	3580	3820	4060	4295	4775	5250	5505	5760	5950	6135
65 KM/H TRIPLE			2810	3045	3280	3510	3745	3980	4215	4680	5150	5400	5650	5830	6015

* IMPORTANT

The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (October 2026). Technical data is subject to change without prior notice.

- For plowing and other field applications subject to high torque, use the 30 km/h line.
- When using single tire configuration:
  - add 0.4 bar for use on slopes of more than 20%
  - add 0.4 bar for intensive road use exceeding 50%
- 10 km/h: low torque application only.